

Technische Daten

USB 8

USB 10

Maximale Ausgangsleistung	160W (80W x 2)	350W (175W x 2)
Nennleistung	100W (50W x2)	175W (85.5W x2)
Ausgangsimpedanz	$2\Omega + 2\Omega$	$2\Omega + 2\Omega$
Trennfrequenz	50~100 Hz	50~100 Hz
Signalrauschabstand	>60dB	>60dB
Maximale Stromaufnahme	12A	12A
Eingangsempfindlichkeit 1%	RCA input 50mV-0.2V Speaker input 0.8V	RCA input 50mV-0.2V Speaker input 0.8V
Betriebsspannung	14.4V (10-16V)	14.4V (10-16V)
Abmessungen	345x240x74mm	369x275x82mm
Gewicht (mit Zubehör)	5 kg	6.5 kg

Technical Specifications USB 8

USB 10

Maximum output power	160W (80W x 2)	350W (175W x 2)
Rated power	100W (50W x2)	175W (85.5W x2)
Output impedance	$2\Omega + 2\Omega$	$2\Omega + 2\Omega$
Crossover frequency	50~100 Hz	50~100 Hz
S/N (A)	>60dB	>60dB
Maximum Current Consumption	12A	12A
Sensitivity (Distortion level 1%)	RCA input 50mV-0.2V Speaker input 0.8V	RCA input 50mV-0.2V Speaker input 0.8V
Source Voltage	14.4V (10-16V)	14.4V (10-16V)
Size	345x240x74mm	369x275x82mm
Weight (including accessories)	5 kg	6.5 kg