



"Haute couture" sound

Elite



# K2 POWER ES 165KX3

## 3-way component kit

### Aluminum chassis new design

- Rigid, antimagnetic with exclusive design for a better excursion

### K2 Power sandwich cone

- Dynamic & precise

### Bi-Amp audiophile crossover

- (Tweeter 0 / +3 / - 3 dB/oct), multi settings
- Reliability and power



### Aluminum tweeter housing

- Flush "high tech" fitting design

### Integrated terminal

- More compact

### Exclusive VC venting system

- High SPL and high power handling

### Butyl surround exclusive patent "TMD" (Tuned Mass Damper) with S/N engraved

- Better control, more neutral and linear sound

### TKMX "M" profile aramid fiber inverted dome tweeter

- High extension in treble
- Smooth and precision

## WHAT MAKES THE DIFFERENCE

- Inverted dome "M"-shaped tweeter
- Bi-Amp crossover
- High power handling
- 3" compact medium size
- Aluminum and mesh grille
- Safe impedance

## TECHNICAL CHARACTERISTICS

### 3-way component kit

**Diameter:** 6 1/2" (165mm)

**Voice coil diameter:** 1 9/16" (40mm)

**Voice coil height:** 0 2/3" (16.5mm)

**Motor:** Magnet

**Tweeter:** TKMX ("M" profile aramid fiber inverted dome)

**Cone:** Composite K2 Power "W" sandwich cone

**Surround:** Tuned Mass Damper (TMD®)

**Separated crossover:** 6-12/12/12dB (3/4/500Hz/3.5kHz)

**Tweeter Adjustable level:** +3; 0; -3dB/oct

**Max.power:** 240W

**Nom.power:** 120W RMS

**Sensitivity (2.83V/1m):** 93dB

**Frequency response:** 45Hz- 22kHz

**Impedance:** 4 Ω

**Accessories:** Supplied grilles and midbox