



CTK Premium Vibrodamping material

Designed for loss of amplitude of body element vibrations

Produced in the form of sheets

Sheet dimensions 500*370 mm

Sheet thickness (mm) – 1.8/2,2/3,0/4,0

Weight 1 m² - (kg) : for thickness 1.8 mm – 2,7
 for thickness 2,2 mm – 3,07
 for thickness 3,0 mm – 3,7
 for thickness 4,0 mm – 4,61

Foil thickness 100 µm

Foil color - black with white printing

Pattern - embossed square

Packing: individual, corrugated cardboard

Use:

Premium 1.8mm and 2,2mm -Ceiling, doors, hood, trunk lid.

Premium 3,0 mm -The ceiling, the door, the bottom of the luggage compartment, passenger compartment floor, engine compartment bulkhead.

Premium 4,0 mm -The wheel arches, the bottom of the luggage compartment, passenger compartment floor.

Weight per 1 Sheet		Weight per SQR.M.			SQR.M. Per Package	
(1.8) 0.5 kg		2,7 kg		16	2.96	248.64
(2.2) 0.57 kg		3,07 kg		15	2.775	233.1
(3.0) 0.69 kg		3,7 kg		12	2.22	186.48
(4.0) 0.85		4,61 kg			1.85	155.4