

...connecting to the aftermarket

CTSNS020.2 Analogue Nissan Steering Wheel Control Interface



Application:

350Z (Coupe/Roadster) 2003 - 2010

For BOSE Amplified Vehicles



CTSNS020.2

Analogue Nissan Steering Wheel Control Interface for Vehicles with BOSE Amplified Systems

Product Contents

- 1. Interface
- 2. Harness
- 3. Amp Pass Through Lead
- 4. Instruction

Prior to installation

Read the manual prior to installation. Technical knowledge is necessary for installation. The place of installation must be free of moisture and away from heat sources. Please ensure you use the correct tools to avoid damage to the vehicle or product.

Connects2 can not be held responsible for the installation of this product.

Wiring Colour Codes

Wire Colour	Function
Yellow	Permanent 12V
Black	Ground
Red	12V Ignition
Orange	Illumination

Wire Colour	Function
Purple	Right Rear Speaker +
Purple/Black	Right Rear Speaker -
Green	Left Rear Speaker +
Green/Black	Left Rear Speaker -
Grey	Right Front Speaker +
Grey/Black	Right Front Speaker -
White	Left Front Speaker +
White/Black	Left Front Speaker -

Technical Support

Connects2 want to provide a fast and suitable resolution should you encounter any technical issues. With this in mind, when contacting Connects2, try to provide as much Information as possible. This will speed up the process and help us to help you.



Subscribe to our YouTube Channel for installation guides and tips... www.youtube.com/connects2

- 1. Remove and disconnect the original head unit.
- 2. Connect the 12 way molex connector of the head unit patch lead (supplied separately) to the interface.



3. Connect the opposite end of head unit patch lead to the head unit steering wheel control input on the back of the aftermarket head unit. This may be a 3.5mm jack plug or a wire input depending upon the head unit brand being fitted.

Please see the head unit installation manual for further information on where to connect.

Important Note: This step must be completed before connecting power to the interface. Failure to so do may result in no steering wheel control function.




4. Connect the 14 way molex connector to the interface



FITTING GUIDE

- 5. Connect both of the female ISO connectors from the Amp Pass Through Lead (a) and the CTSVW020.2 (b) to the male ISO connector from the aftermarket head unit (c)
- 6. Connect the male connector from the Amp Pass Through Lead (d) to the remaining female ISO connector from the CTSVW020.2 (e)



7. Connect the female vehicle specific connector to the male vehicle connector. Test head unit for correct operation.

STEERING WHEEL CONTROL FUNCTIONS

