



Connects2Vision

User Manual

CAM-LX3-AD Reverse Camera Add On Interface For select Lexus and Toyota vehicles

APPLICATION:

Lexus GS Series (3rd Gen/S190)	2005 - 2011
Lexus IS Series (2nd Gen/XE20)	2005 - 2013
Lexus LS Series (4th Gen/XF40)	2007 - 2017
Toyota Landcruiser 200 (v8)	2008 - 2011

Allows for the addition of an aftermarket reverse camera to the original vehicle screen. This harness works with models which feature either an OEM factory Toyota system, or MFD GEN5 Lexus multi-displays.

Note: the camera being paired with this product must be NTSC.

DISCLAIMER:

Prior to Installation

Read the manual prior to installation. Technical knowledge is necessary for installation. The place of installation must be free of moisture and away from heat sources. Please ensure you use the correct tools to avoid damage to the vehicle or product.

Connects2 can not be held responsible for the installation of this product.

- Reverse Camera Add On Adapter
- 2x Male Bullet Connectors
- Instructions

INSTALLATION

1. Remove the vehicles head unit by following the manufacturer's instructions/ guidelines. Once removed, disconnect all the power connections including the 28-pin connector.

2. With the aftermarket camera installed, connect this to the yellow RCA of the CAM-LX3-AD.

3. Connect the red & black 6V wires if the camera being used needs an 6V power supply.

Note: this step only needs to be carried out if you are installing a camera that needs a 6V power supply.

4. Attach the 28-pin specific connectors to the back of the head unit and to the OEM vehicle connection. When done, connect the power and test the reverse camera's functionality before reassembling the dashboard.