

Connects2Vision

User Manual

Reverse Camera Retention Interface For select Isuzu & Suzuki vehicles

APPLICATION:

Isuzu D-Max (RT50)	2012-2015
Isuzu MU-X	2013-2020
Suzuki Baleno	2015 >
Suzuki Kizashi	2009-2014
Suzuki SX4 S-Cross	2013 >

 Isuzu D-Max (RT50 Facelift) 2021 >

 Suzuki Alto
 2009 >

 Suzuki Jimny
 2018 >

 Suzuki Swift
 2010-2017

 Suzuki Vitara (MK4/LY)
 2015 >

Allows for the retention of the factory OEM reverse camera when upgrading to an aftermarket head unit. This lead is compatible with vehicles which feature OEM touch screen units.

DISCLAIMER:

Prior to Installation

Read the manual prior to installation. Technical knowledge is necessary for installation. The place of installation must be free of moisture and away from heat sources. Please ensure you use the correct tools to avoid damage to the vehicle or product.

Connects2 can not be held responsible for the installation of this product.

- Reverse Camera Retention Adapter
- Instructions

INSTALLATION

1. Remove the vehicles head unit by following the manufacturer's instructions/ guidelines. Once removed, disconnect all the power connections.

2. Connect the female 8-way ISO connector from the CAM-SZ2-RT to a separate ISO T-harness or steering wheel control harness (sold separately).

3. Connect the vehicles green 5-way reverse camera connector to the equivalent found on the CAM-SZ2-RT.

4. Connect the male Yellow RCA jack to the rear camera input of the aftermarket radio.

5. Connect the 8-way ISO connector to the head unit. When done, proceed to connect the main power and test the reverse camera's functionality before reassembling the dashboard.

Note: when testing the head unit, ensure that within the 'camera settings' menu, the camera preset is set to on (the location of this setting will differ from head unit manufacturer).