

EINBAUMASSE INSTALLATION DIAMETER



	EINBAUTIEFE MOUNTING DEPTH		AUSSCHNITT Ø INSTALLATION Ø				AUSSEN Ø EXTERNAL Ø	
	Hochtöner Tweeter	Tieftöner Woofers	Hochtöner Tweeter	Tieftöner Woofers	Hochtöner Tweeter	Tieftöner Woofers	Hochtöner Tweeter	Tieftöner Woofers
M - LINE	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm
MS 5008	0.39/0.83 10/21	2.19 55,5	1.77 45	4.49 114	1.93 49	5.12 130		
MS 6508	0.39/0.83 10/21	2.50 63,5	1.77 45	5.61 142,5	1.93 49	6.54 166		
MS 6508 ACTIVE	0.39/0.83 10/21	2.50 63,5	1.77 45	5.61 142,5	1.93 49	6.54 166		
MS 654010	0.39/0.83 10/21	2.50 63,5	1.77 45	5.61 142,5	1.93 49	6.54 166		
MS 654010 ACTIVE	Mitteltöner / Midrange:	1.71 43,5	Mitteltöner / Midrange:	3.39 86	Mitteltöner / Midrange:	3.96 100,5		
STATUS	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm
ST 40 WS	0.39/0.83 10/21	–	1.77 45	–	1.93 49	–		
SV 4009	0.39/0.83 10/21	1.81 45,5	1.77 45	3.39 86	1.93 49	3.96 100,5		
SV 5009	0.39/0.83 10/21	2.40 61	1.77 45	4.49 114	1.93 49	5.12 130		
SV 6509	0.39/0.83 10/21	2.50 63,5	1.77 45	5.61 142,5	1.93 49	6.54 166		
SV 6509 ACTIVE	0.39/0.83 10/21	2.50 63,5	1.77 45	5.61 142,5	1.93 49	6.54 166		
SW 6509	–	2.50 63,5	–	5.61 142,5	–	6.54 166		
E P I C	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm
ET 20 WS	0.22/0.49 5,5/12,5	–	0.93 23,5	–	1.48 37,5	–		
EV 4008	0.22/0.49 5,5/12,5	1.81 45,5	0.93 23,5	3.39 86	1.48 37,5	3.96 100,5		
EV 5008	0.22/0.49 5,5/12,5	2.40 61	0.93 23,5	4.49 114	1.48 37,5	5.12 130		
EV 6508	0.22/0.49 5,5/12,5	2.50 63,5	0.93 23,5	5.61 142,5	1.48 37,5	6.54 166		
ES 804010	0.22/0.49 5,5/12,5	3.23 82	0.93 23,5	7.24 184	1.48 37,5	8.19 208		
	Mitteltöner / Midrange:	1.27 32,25	Mitteltöner / Midrange:	3.39 86	Mitteltöner / Midrange:	3.96 100,5		
EV 6808	0.22/0.49 5,5/12,5	2.52 64	0.93 23,5	6" x 8" oval *	1.48 37,5	–		
EV 6908	0.22/0.49 5,5/12,5	3.25 83	0.93 23,5	6" x 9" oval **	1.48 37,5	–		
ES 8009	0.22/0.49 5,5/12,5	3.23 82	0.93 23,5	7.24 184	1.48 37,5	8.19 208		
EFS 4008	0.28/0.73 7/18,5	1.27 32,25	1.46 37	3.39 86	1.77 44,5	3.96 100,5		
EFS 5008	0.28/0.73 7/18,5	1.66 42,25	1.46 37	4.49 114	1.77 44,5	5.12 130		
EFS 6508	0.28/0.73 7/18,5	1.78 45,25	1.46 37	5.61 142,5	1.77 44,5	6.54 166		
C O N C E P T	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm
CS 4008	0.3/0.7 7,5/18	1.71 43,5	1.22 31	3.39 86	1.57 40	3.96 100,5		
CS 5008 CS 5008 IV 2 Ohm	0.3/0.7 7,5/18	2.32 59	1.22 31	4.49 114	1.57 40	5.12 130		
CS 6508 CS 6508 IV CS 6508 IV 2 Ohm	0.3/0.7 7,5/18	2.42 61,5	1.22 31	5.61 142,5	1.57 40	6.54 166		
CS 654010	0.3/0.7 7,5/18	2.42 61,5	1.22 31	5.61 142,5	1.57 40	6.54 166		
	Mitteltöner / Midrange:	1.71 43,5	Mitteltöner / Midrange:	3.39 86	Mitteltöner / Midrange:	3.96 100,5		
CC 4008	–	1.71 43,5	–	3.39 86	–	3.96 100,5		
CC 5008 CC 5008 IV 2 Ohm	–	2.32 59	–	4.49 114	–	5.12 130		
CC 6508 CC 6508 IV 2 Ohm	–	2.42 61,5	–	5.61 142,5	–	6.54 166		
CC 6808	–	2.28 58	–	6" x 8" oval *	–	–		
CC 6908	–	3.09 78,5	–	6" x 9" oval **	–	–		
A L P H A	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm
AS 5008	0.31/0.63 8/16	2.4 62	1.22 31	4.65 118	1.59 40,5	5.12 130		
AS 6508	0.31/0.63 8/16	2.6 67	1.22 31	5.6 143	1.59 40,5	6.54 166		
AC 5008	–	2.4 62	–	4.65 118	–	5.12 130		
AC 6508	–	2.6 67	–	5.6 143	–	6.54 166		
AC 6908	–	3.2 81	–	6" x 9" oval **	–	–		
2 - S E R I E S	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm
2S 6512	0.63/- 16/-	2.32 59	1.97 50	5.51 140	2.28 58	6.56 166,5		
2C 6512	–	2.32 59	–	5.51 140	–	6.56 166,5		
M A R I N A - R	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm
MRC 6508	–	2.50 63,5	–	5.79 147	–	6.73 171		
MRC 6908	–	3.25 83	–	5.9x8.7 150x220	–	6.71x9.56 170,5x243		
MRW 10008	–	4.61 117	–	8.94 227	–	10.71 272		
MRC 10008 D	–	4.61 117	–	8.94 227	–	10.71 272		
S P E C I A L S	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm	inch mm
SWF 8012 HE	–	2.28 58	–	7.2 183	–	8.23 209		
SW 10009	–	4.61 117	–	8.94 227	–	10.71 272		
SW 8010 HE	–	3.23 82	–	7.24 184	–	8.19 208		
SW 8009	–	3.23 82	–	7.24 184	–	8.19 208		
FS 5009 ST	0.39/0.83 10/21	1.66 42,25	1.77 45	4.49 114	1.93 49	5.12 130		
FS 6509 ST	0.39/0.83 10/21	1.78 45,25	1.77 45	5.61 142,5	1.93 49	6.54 166		

* Speziell für original Einbauschächte. Especially for original installation slots.

** Außendurchmesser! Ausschnittsdurchmesser nur von der Original-Einbauschablone entnehmen.
External diameter! Installation diameters you will find on installation template.